

# Yabby Edge Cellular

Cellular LTE-M / NB-IoT

Low cost, Indoor and Outdoor asset tracker with industry-leading battery life in a small rugged IP67 housing



**Global Coverage**

Operates in 220+ countries and territories, including all major markets in North America, Europe, and Asia.



**3-5 Year Battery Life**

Long battery life to support large-scale deployments in remote areas.



**Asset Tracking**

Real-time location tracking and geofencing capabilities for fleet management.



**Ultra-Rugged**

Weatherproof and ultra-rugged IP67 Housing



**Low Cost**

Low cost to support large-scale deployments

## Connectivity

LTE-M / NB-IoT	Nordic nRF9160 Modem operates on all major global LTE-M and NB-IoT bands. Supported LTE-M (Cat-M1) bands: Cat-M1: B1, B2, B3, B4, B5, B8, B12, B13, B14, B17, B18, B19, B20, B25, B26, B28, B66 Cat-NB1/NB2: B1, B2, B3, B4, B5, B8, B12, B13, B17, B19, B20, B25, B26, B28, B66
SIM Size & Access	Internal Nano 4FF SIM

## Batteries

User-Replaceable Batteries	3 x AAA
Battery Life	Up to 5 years of battery life at once-daily position updates, 1 year battery life at once-hourly position updates. Enable intelligent movement-based tracking for longer battery life.
Supported Battery Types	Alkaline Lithium (LiFeS2) - recommended *Please dispose of Lithium batteries in a safe and responsible manner

## Location

Chipset	Semtech LR1110
Constellation	GPS and BeiDou
Cloud-Based Solver	Asset location is calculated using Semtech's Cloud-Based solver and optionally Digital Matter's Location Engine for simple integration
Tracking Sensitivity	-134 dBm autonomous / -141 dBm aided
GNSS Assistance	GNSS almanac data for greater sensitivity and position accuracy
Low Noise Amplifier	GPS signals are boosted by a unique low-noise amplifier (LNA) allowing operation where other units fail
WiFi Positioning	Indoor asset location using WiFi access point scanning
Cell Tower Location (planned)	Cell tower fallback for positioning when there is no GNSS or WiFi signal

## Power

Input Voltage	3-5.5V DC
Sleep Current	<10uA* *Average current in lowest power configuration

## Mechanics / Design

Dimensions	Standard - 85 x 63 x 24 mm (3.35 x 2.48 x .94") Livestock Collar - 109 x 60 x 30 (4.29 x 2.36 x 1.18") Snap Housing (Smallest Size, not IP67 rated) - 75 x 45 x 25 mm (2.95 x 1.77 x 0.98")
Weight	Standard - 82 g (2.9 oz)
Housing	Ultra-Rugged IP67 Housing

## Mechanics / Design *(continued)*

---

IP Rating	IP67 rated housing ensures device can withstand fine dust, high-pressure spray, submersion for 30 mins in 1m of water, and extreme temperatures
Installation	Compact and concealable. Multiple installation options for covertly and easily securing the device to assets with screws, bolts, cable ties, rivets, and more. Collar housing available for securing device to livestock.
Operating Temperature	-20°C to +60°C
GPS Antenna	Internal
Cellular Antenna	Internal
WiFi Antenna	Internal
3-Axis Accelerometer	3-Axis Accelerometer to detect movement, high G-force events, and more
Diagnostic LED	Diagnostic LED signifies operation status
Flash Memory	Store weeks of records if device is out of cellular coverage. Storage capacity for over 5 days of continuous 30-second logging.

---

## Smarts

---

Auto-APN	Auto-APN allows the device to analyze the SIM card and select the correct APN details from a list that is pre-loaded in the device's firmware
Geofence Alerts	The server can use device location to create geofences and alerts if an asset enters or leaves designated locations
Impact Detection	Configure impact-detection alerts when G-forces are exceeded by a user-defined threshold
Periodic or Movement-Based Tracking	Configure parameters to send updates based on set time intervals or when movement occurs. Adaptive tracking technology detects when the device is on the move and increases the update rate, providing detail when you need it while conserving battery when stationary.
Run Hour Monitoring	Capture run hours based on movement to understand and optimize asset utilization
Sleep Mode	Stationary devices enter sleep mode until movement occurs to conserve battery life and optimize data usage
Theft Recovery	Switch to Recovery Mode in the case of theft or loss to activate real-time tracking for asset retrieval

---

## Device Management

---

Flexible Configuration	Configure device parameters such as position update rate, movement and accelerometer settings, and more to fit any tracking application
OEM Server	Manage, monitor, configure, debug, update, and restart devices remotely from our cloud-based device management system

---

# Integration

---

Third-Party Integration	TCP Direct or HTTPS Webhook
Cloud-Based Solver	Digital Matter's Location Engine makes it easy to perform the cloud based position solving and integrate data into any system. Cloud-based solving may also be performed in user's own platform.

---

# Security

---

Data Security	Military-level AES-256 Encryption from device to OEM Server to protect the integrity and confidentiality of telematics data. Data forwarded to third-party systems is sent via HTTPS for end-to-end security.
---------------	--

---

# Warranty

---

Manufacturer's Warranty	One year manufacturer's warranty
-------------------------	----------------------------------

---

# Certifications

---

Please contact us for a full list of compliance specifications and documentation for your region.	Coming Soon
---	-------------

---